

■ RIFLE, LOAD AND CONDITIONS

RIFLE (MAKE, MODEL, SERIAL)		BARREL / TWIST	UNITS / CLICK VALUE ☐ MIL ☐ MOA
OPTIC AND RETICLE (FFP / SFP)		ZERO DISTANCE	SIGHT HEIGHT (BORE TO OPTIC)
CARTRIDGE	BULLET (WEIGHT, TYPE)	BC (G1 / G7)	MUZZLE VELOCITY (CHRONO)
AMMO LOT	TEMPERATURE	ALTITUDE	STATION PRESSURE
DENSITY ALTITUDE	HUMIDITY	DATA TRUED ON	COLD BORE

HOLDS BY DISTANCE holds in your units from the reticle center, level shot

[illegible]

Wind value: 3 and 9 o'clock = full value. 1:30, 4:30, 7:30 and 10:30 $\approx$ 0.7. 12 and 6 = none. Wind hold scales with speed: 5 mph is half the 10 mph hold, 15 mph is 1.5 $\times$.

Mark rows Confirmed only after you've shot them. Calculated data is a starting point; re-true when conditions change a lot. SFP: holds are true only at the calibrated magnification.

✂ CUT OUT FOR YOUR STOCK OR SCOPE CAP ✂

[illegible][illegible]